

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-2144477-1  
**Report Reference** E525409-20211129  
**Date** 9-Dec-2021

**Issued to:** LITEK Srl  
via delle Industrie 3b Poggio Torriana, RN  
Italy 47824

**This is to certify that representative samples of** IFAR7 - Light-emitting-diode Luminaire Retrofit Kits  
Certified for Canada

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** CSA C22.2 NO. 250.1-16, 1st Ed., Issue Date: 2016-06-01

**Additional Information:** See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-2144477-1  
**Report Reference** E525409-20211129  
**Date** 9-Dec-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
<p><b>Modulo universale 2.0, MX025, AA BBB CC DDD E F G H_UL</b></p> <p>Where:</p> <p>AA is a 2 digits code that represents the series type as follows: -MX: Series Modulo Universale 2.0</p> <p>BBB is a 3 digits code that represents the wattage version as follows: -030: model MX030 -040: model MX040 -046: model MX046 -025: model MX025 -035: model MX035</p> <p>CC is a 2 digits code that represents the optic version as follows: -AA, -AC, -AD, -AG, -AH, -BL, -AN, -AL, -AI, -AQ, -AS</p> <p>DDD is a 3 digit code that represents the LED current as follows: -350: 350 mA -450: 450 mA -510: 510 mA -530: 530 mA -700: 700 mA</p> <p>E is a 1 digit code that represents the light temperature color as follows: -1: 2200K -2: 2700K -3: 3000K -4: 4000K</p> <p>F is a 1 digit code that represents the paint color as follows: -B</p>	LED Luminaire Retrofit Kits



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-2144477-1  
**Report Reference** E525409-20211129  
**Date** 9-Dec-2021

<p>G is a 1 digit numerical code that represents the luminaire control as follows: - -1, -3, -4, -7, -8, -9</p> <p>H is a 1 digit numerical code that represents the output type as follows: - -3: Class 2</p>	
<p><b>Modulo universale 2.0</b>, MX030, AA BBB CC DDD E F G H_UL</p> <p>Where:</p> <p>AA is a 2 digits code that represents the series type as follows: -MX: Series Modulo Universale 2.0</p> <p>BBB is a 3 digits code that represents the wattage version as follows: -030: model MX030 -040: model MX040 -046: model MX046 -025: model MX025 -035: model MX035</p> <p>CC is a 2 digits code that represents the optic version as follows: -AA, -AC, -AD, -AG, -AH, -BL, -AN, -AL, -AI, -AQ, -AS</p> <p>DDD is a 3 digit code that represents the LED current as follows: -350: 350 mA -450: 450 mA -510: 510 mA -530: 530 mA -700: 700 mA</p> <p>E is a 1 digit code that represents the light temperature color as follows: -1: 2200K -2: 2700K -3: 3000K -4: 4000K</p> <p>F is a 1 digit code that represents the paint color as follows: -B</p>	LED Luminaire Retrofit Kits



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>





# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-2144477-1  
**Report Reference** E525409-20211129  
**Date** 9-Dec-2021

<p>G is a 1 digit numerical code that represents the luminaire control as follows: - -1, -3, -4, -7, -8, -9</p> <p>H is a 1 digit numerical code that represents the output type as follows: - -3: Class 2</p>	
<p><b>Modulo universale 2.0</b>, MX035, AA BBB CC DDD E F G H_UL</p> <p>Where:</p> <p>AA is a 2 digits code that represents the series type as follows: -MX: Series Modulo Universale 2.0</p> <p>BBB is a 3 digits code that represents the wattage version as follows: -030: model MX030 -040: model MX040 -046: model MX046 -025: model MX025 -035: model MX035</p> <p>CC is a 2 digits code that represents the optic version as follows: -AA, -AC, -AD, -AG, -AH, -BL, -AN, -AL, -AI, -AQ, -AS</p> <p>DDD is a 3 digit code that represents the LED current as follows: -350: 350 mA -450: 450 mA -510: 510 mA -530: 530 mA -700: 700 mA</p> <p>E is a 1 digit code that represents the light temperature color as follows: -1: 2200K -2: 2700K -3: 3000K -4: 4000K</p> <p>F is a 1 digit code that represents the paint color as follows: -B</p>	LED Luminaire Retrofit Kits



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-2144477-1  
**Report Reference** E525409-20211129  
**Date** 9-Dec-2021

<p>G is a 1 digit numerical code that represents the luminaire control as follows: - -1, -3, -4, -7, -8, -9</p> <p>H is a 1 digit numerical code that represents the output type as follows: - -3: Class 2</p>	
<p><b>Modulo universale 2.0</b>, MX040, AA BBB CC DDD E F G H_UL</p> <p>Where:</p> <p>AA is a 2 digits code that represents the series type as follows: -MX: Series Modulo Universale 2.0</p> <p>BBB is a 3 digits code that represents the wattage version as follows: -030: model MX030 -040: model MX040 -046: model MX046 -025: model MX025 -035: model MX035</p> <p>CC is a 2 digits code that represents the optic version as follows: -AA, -AC, -AD, -AG, -AH, -BL, -AN, -AL, -AI, -AQ, -AS</p> <p>DDD is a 3 digit code that represents the LED current as follows: -350: 350 mA -450: 450 mA -510: 510 mA -530: 530 mA -700: 700 mA</p> <p>E is a 1 digit code that represents the light temperature color as follows: -1: 2200K -2: 2700K -3: 3000K -4: 4000K</p> <p>F is a 1 digit code that represents the paint color as follows: -B</p>	LED Luminaire Retrofit Kits



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-2144477-1  
**Report Reference** E525409-20211129  
**Date** 9-Dec-2021

<p>G is a 1 digit numerical code that represents the luminaire control as follows: - -1, -3, -4, -7, -8, -9</p> <p>H is a 1 digit numerical code that represents the output type as follows: - -3: Class 2</p>	
<p><b>Modulo universale 2.0</b>, MX046, AA BBB CC DDD E F G H_UL</p> <p>Where:</p> <p>AA is a 2 digits code that represents the series type as follows: -MX: Series Modulo Universale 2.0</p> <p>BBB is a 3 digits code that represents the wattage version as follows: -030: model MX030 -040: model MX040 -046: model MX046 -025: model MX025 -035: model MX035</p> <p>CC is a 2 digits code that represents the optic version as follows: -AA, -AC, -AD, -AG, -AH, -BL, -AN, -AL, -AI, -AQ, -AS</p> <p>DDD is a 3 digit code that represents the LED current as follows: -350: 350 mA -450: 450 mA -510: 510 mA -530: 530 mA -700: 700 mA</p> <p>E is a 1 digit code that represents the light temperature color as follows: -1: 2200K -2: 2700K -3: 3000K -4: 4000K</p> <p>F is a 1 digit code that represents the paint color as follows: -B</p>	LED Luminaire Retrofit Kits



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>





# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-2144477-1  
**Report Reference** E525409-20211129  
**Date** 9-Dec-2021

G is a 1 digit numerical code that represents the luminaire control as follows:  
- -1, -3, -4, -7, -8, -9

H is a 1 digit numerical code that represents the output type as follows:  
- -3: Class 2



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

